

XLGV High Volume

XLGV Pump Type <table><tr><th>Code</th><th>Description</th></tr><tr><td>XLGV</td><td>High Volume Grinder Hazardous Location</td></tr></table>	Code	Description	XLGV	High Volume Grinder Hazardous Location	07 Horsepower <table><tr><th>Code</th><th>Description</th></tr><tr><td>07</td><td>7.5 hp</td></tr></table>	Code	Description	07	7.5 hp	Voltage <table><tr><th>Code</th><th>Description</th></tr><tr><td>3</td><td>200/230V 3Ø-208V or 240V system</td></tr><tr><td>4</td><td>460V 3Ø-480V system</td></tr><tr><td>5</td><td>575V 3Ø-600V system</td></tr></table>	Code	Description	3	200/230V 3Ø-208V or 240V system	4	460V 3Ø-480V system	5	575V 3Ø-600V system	A Frequency Hz <table><tr><th>Code</th><th>Description</th></tr><tr><td>A</td><td>60 Hz</td></tr></table>	Code	Description	A	60 Hz	Impeller Size <table><tr><th>Code</th><th>Description</th></tr><tr><td>0620</td><td>6.2"</td></tr></table>	Code	Description	0620	6.2"	S Impeller Material <table><tr><th>Code</th><th>Description</th></tr><tr><td>S</td><td>Stainless Steel</td></tr></table>	Code	Description	S	Stainless Steel	2 Seal Config <table><tr><th>Code</th><th>Description</th></tr><tr><td>2</td><td>Dual Seal</td></tr></table>	Code	Description	2	Dual Seal	Lower Seal <table><tr><th>Code</th><th>Description</th></tr><tr><td>S</td><td>Silicon Carbide on Silicon Carbide</td></tr><tr><td>T</td><td>Tungsten Carbide on Tungsten Carbide</td></tr></table>	Code	Description	S	Silicon Carbide on Silicon Carbide	T	Tungsten Carbide on Tungsten Carbide	Discharge <table><tr><th>Code</th><th>Description</th></tr><tr><td>BJ</td><td>Horizontal, 2", 2.5" & 3", 150# ANSI, & 2" NPT</td></tr><tr><td>FB</td><td>Vertical, 2" & 3" NPT</td></tr></table>	Code	Description	BJ	Horizontal, 2", 2.5" & 3", 150# ANSI, & 2" NPT	FB	Vertical, 2" & 3" NPT	Cord Type <table><tr><th>Code</th><th>Description</th></tr><tr><td>A</td><td>Permanent</td></tr><tr><td>B</td><td>Heavy-duty Quick-connect</td></tr></table>	Code	Description	A	Permanent	B	Heavy-duty Quick-connect	Cord Length <table><tr><th>Code</th><th>Description</th></tr><tr><td>-3</td><td>35'</td></tr><tr><td>-5</td><td>50'</td></tr><tr><td>-1</td><td>100'</td></tr></table>	Code	Description	-3	35'	-5	50'	-1	100'
Code	Description																																																																			
XLGV	High Volume Grinder Hazardous Location																																																																			
Code	Description																																																																			
07	7.5 hp																																																																			
Code	Description																																																																			
3	200/230V 3Ø-208V or 240V system																																																																			
4	460V 3Ø-480V system																																																																			
5	575V 3Ø-600V system																																																																			
Code	Description																																																																			
A	60 Hz																																																																			
Code	Description																																																																			
0620	6.2"																																																																			
Code	Description																																																																			
S	Stainless Steel																																																																			
Code	Description																																																																			
2	Dual Seal																																																																			
Code	Description																																																																			
S	Silicon Carbide on Silicon Carbide																																																																			
T	Tungsten Carbide on Tungsten Carbide																																																																			
Code	Description																																																																			
BJ	Horizontal, 2", 2.5" & 3", 150# ANSI, & 2" NPT																																																																			
FB	Vertical, 2" & 3" NPT																																																																			
Code	Description																																																																			
A	Permanent																																																																			
B	Heavy-duty Quick-connect																																																																			
Code	Description																																																																			
-3	35'																																																																			
-5	50'																																																																			
-1	100'																																																																			

Denotes Standard Construction

XLGH High Head

X

L

G

H

Pump Type

Code	Description
XLGH	High Head Grinder Hazardous Location

0

7

Horsepower

Code	Description
07	7.5 hp

Voltage

Code	Description
3	200/230V 3Ø-208V or 240V system
4	460V 3Ø-480V system
5	575V 3Ø-600V system

A

Frequency Hz

Code	Description
A	60 Hz

Impeller Size

Code	Description
0740	7.4"

S

Impeller Material

Code	Description
S	Stainless Steel

2

Seal Config

Code	Description
2	Dual Seal

Lower Seal

Code	Description
S	Silicon Carbide on Silicon Carbide
T	Tungsten Carbide on Tungsten Carbide

Discharge

Code	Description
BJ	Horizontal, 2", 2.5" & 3", 150# ANSI, & 2" NPT
FB	Vertical, 2" & 3" NPT

Cord Type

Code	Description
A	Permanent
B	Heavy-duty Quick-connect

Cord Length

Code	Description
-3	35'
-5	50'
-1	100'

Denotes Standard Construction

Specifications are subject to change without notice.