LCU-Series Condensate Pumps

Liberty Pumps

A Family and Employee Owned Company





A Family and Employee Owned Company

A model for every application




LCU-15 Series

Condensate Pumps

For removal of condensate from high efficiency furnaces, A/C equipment, ice machines, drinking fountains, beverage machines, dehumidifiers, and other applications requiring condensate removal.

Performance Curves







LCU-20 Series

 Γ

Updated Design!

Features


- High impact ABS tank
- Visual bubble level
- Wall mounts
- Four 1" intake holes
- 3/8" O.D. outlet
- Barbed discharge connection
- Serviceable check valve
- Stainless steel shaft
- 6' Power cord with ground
- Thermally protected
- Fully automatic
- Quiet operation
- Isolation pads pre-installed on tank
- Models with an "S" include built-in safety switch
- Models with a "T" include 20' of tubing



LCU-SP Series

Shallow Pan Condensate Pump

The low profile tank design on the LCU-SP model allows for mounting in tight areas; like drain pans and inside furnaces and other equipment. Available in 115 and 230V.





Features

- High impact ABS tank
- Wall mounts
- Three 1" intake holes
- 3/8" O.D. outlet
- Barbed and threaded discharge connection
- Removable check valve
- Stainless steel shaft
- 6' Power cord with ground

- Thermally protected
- Fully automatic
- Quiet operation
- Isolation pads pre-installed on tank
- Models with an "S" include built-in safety switch
- Models with a "T" include 20' of tubing



LCU-N Series

Neutralizing Condensate Pump

For neutralization and removal of acidic condensate (up to 500,000 BTUs) produced by high-efficiency combustion equipment. When not neutralized, acidic condensate has the potential to harm the environment and many materials it comes in contact with due to its acidic nature.

Performance Curve



Easy to replace neutralizer cartridge Model LCU-N22OST Shown (Includes 20' of discharge tubing)



LCU-PR Series

Plenum Rated Condensate Pumps

115V or 230V

60 Hz

22' Maximum Head

Designed for removal of condensate from air conditioning, refrigeration, and dehumidification equipment installed in air-handling and plenum applications having limited space.

The LCU-PR meets UL Standard 2043 for plenum applications.


Features

- Plenum rated
- Indicator lights
- Overflow safety switch
- Four inlets

- Vibration dampening feet and motor mounts
- Meets UL Standard 2043



Performance Curve



LCU-MS Series

Mini-Split Condensate Pump

For removal of condensate from wall mount, ductless mini-split air systems up to 23,500 Btu (7 kW), fan coils, and suspended ceiling air conditioners.



Features

- Quiet operation
- Solid-state switch technology
- Normally closed relay rated at 3A resistive 250V alarm
- Double-sided adhesive pad and cable ties are supplied to secure pump and reservoir
- 5/16" (7.9 mm) pump discharge outlet
- 5' (1.5 m) power cable
- 5' (1.5 m) communication cable
- 5' (1.5 m) high water safety switch cable
- 5' (1.5 m) hose tubing



Models

- LCU-MS
- LCU-MS2 (includes line cover kit)

Intertek 4007096


Model Selection

MODEL



SAFTEY SWITCH 20' TUBING KIT





AMPS

CAPACITY

VOLTS

HP

	MODEL	HP	VOLTS	AMPS	CAPACITY	SAFTEY SWITCH	20' TUBING KIT			
	LCU-N Series									
	LCU-N20ST	1/30	115	1.5	2 US Qt	Yes	Yes			
	LCU-N220ST	1/30	230	0.7	2 US Qt	Yes	Yes			

K001898 - Replacement neutralizing cartridge



MODEL		VOLTS	AMPS	CAPACITY	SAFTEY SWITCH	
	LCU-PR Series					
	LCU-PR20S	115	1.9	1.5 US Qt	Yes	
	LCU-PR220S	230	1.0	1.5 US Qt	Yes	



LCU-MS Series

LCU-MS - Mini-split condensate pump

LCU-MS2 - Mini-split condensate pump with line cover kit

www.LibertyPumps.com

Model LCU-MS2 Shown



A Family and Employee Owned Company

 7000 Apple Tree Avenue
 Bergen, New York 14416

 Phone 800-543-2550
 Fax 585-494-1839

www.LibertyPumps.com



Specifications subject to change without notice. Copyright © Liberty Pumps, Inc. 2024 All rights reserved. LLIT006840 R02/24



innovate. evolve.